

TL 5-1074-2022

Issue No.: 3

Uncontrolled printing

Effective from: 16.11.2024

Flat component - Patch

PRODUCT DESCRIPTION

Patch is a round cutout or cutout with round corners made from waterproofing membranes.

TECHNICAL PARAMETERS

The technical parameters of waterproofing membranes from which the components are produced are listed in the data sheets of the individual types of membranes.

MEMBRANE TYPE, DIMENSIONS, COLOUR

The membrane used				Patch size
Name	Thickness	Colour ¹⁾		
FATRAFOL 803S	2.00	signal yellow	~ B4013 ²⁾	ø 160 mm ± 2 mm
FATRAFOL 803	2.00	brown	~ RAL 8025	
FATRAFOL 804	2.00	red	~ RAL 3016	
		blue	~ RAL 5015	
		green	~ RAL 6000	
		dark grey	~ RAL 7012	
		black-grey	~ RAL 7016	
		black-grey	~ RAL 7021	
		light grey	~ RAL 7035	
		light grey	~ RAL 7040	
		copper brown	~ RAL 8004	
		brown	~ RAL 8025	
		white	~ RAL 9010	
black	~ RAL 9011			
AQUAPLAST 805 GEO	2.00	green	~ RAL 6000	
		khaki	~ RAL 6006	
		olive	~ RAL 6014	
		black	~ RAL 9011	
EKOPLAST 806	1.50	black	~ RAL 9011	ø 160 mm ± 2 mm ø 115 mm ± 2 mm 305 x 225 mm ± 2 mm 500 x 500 mm ± 2 mm
FATRAFOL 807	2.60	light grey	~ RAL 7035	
FATRAFOL 810	1.50	light grey	~ RAL 7035	305 x 225 mm ± 2 mm 500 x 500 mm ± 2 mm
		dark grey	~ RAL 7012	

¹⁾ Different colour shade of various batches of surfaces of the membranes may vary. Minor differences of colour shade do not constitute the matter for a possible claim.

²⁾ internal designation (RAL not specified)

USAGE

The patch is used to cover fasteners or damaged spots of a waterproofing membrane.
The patch of FATRAFOL 807 is intended only for adhering thermal insulation.

APPLICATION

The laying of components can be made by specialized firms whose workers have been trained properly.

The components are applied conformable with fundamentals being set and described in a Construction and Technologic Instruction FATRAFOL-S, FATRAFOL-H a FATRAFOL-A, being valid in the time of waterproofing providing, available on www.fatrafol.cz.

PACKAGING

The components \varnothing 160 mm	50 pcs in PE bag, 400 pc in cardboard box
	60 pcs in PE bag, 240 pc in cardboard box (FATRAFOL 807)
The components \varnothing 115 mm	60 pcs in PE bag, 1080 pc in cardboard box
The components 305 x 225 mm	200 pcs in cardboard box
The components 500 x 500 mm	on a pallet in 2 columns of 500 pcs each

STORAGE

Store at temperatures between -5 °C and +30 °C. On the site, it is necessary to protect the membrane against pollution. It is recommended to protect the membrane against weather effects until it is applied on the roof.

APPROVALS / CERTIFICATES

Listed in the technical data sheets for individual types of waterproofing membranes.

MORE INFORMATION

More information can be found on the manufacturer's website www.fatrafol.cz.

LEGAL CLAUSE

The technical data contained herein are based on our current knowledge and experience and relate to the use of products under normal application conditions. The information that is included in the current technical data sheet is provided according to a method of use and is incomplete. Before using this product, the user has to check whether the product is suitable for intended use. In addition to that, all the users should contact the dealer or manufacturer of this product to obtain further technical information regarding its use if they are of the opinion that the information available to them requires any explanation, for both the normal and specific use of this product. Please always check that you have the latest version of the product technical data sheet at your disposal. This data sheet and further information can be obtained from the sales or technical representative of the manufacturer or at the website of the producer.

PRODUCER

Fatra, a. s., třída Tomáše Bati 1541, 763 61 Napajedla, Czech Republic
tel.: +420 577 50 3325 (1111)
e-mail: studio@fatrafol.cz
<http://www.fatrafol.cz>



